



All dimensions are nominal. Illustration may be shown with optional equipment.

Standard Features

Hitch/Tongue

- Adjustable Height Hitch with Bolt-on Coupler
- 3" Pintle Ring
- 7-Pole RV Plug
- One-Piece Cold-Formed I-Beam Frame Rails
- Integrated Storage Tray (Lockable Lid Optional)
- 12K Bolt-On, Side-Wind, Drop-Leg Parking Jack
- Battery Break-Away Kit with Tow Charger and Test Light
- Safety Chains with Hooks

Frame/Deck

- 82" Between Fenders (84" Open Fender Available)
- 24" Deck Height (Fully Loaded)
- 10" I-Beam Main Frame
- 3" Jr. I-Beam Crossmembers, 80,000 PSI
- 2" Nominal White Oak Wood Deck
- 3" Tall Side Up
- D-Rings (4 Per Side)
- 12 Gauge One-Piece Formed Fender/Panel

Ramps/Tail

- 18" x 6'-0" Channel Sides, Cleated Ladder Style
- Spring-Assist
- Solid Bar Ramp Hold-Ups
- Load Angle: 18°

Axles/Suspension

- Rubber-Ride Torsion Suspension Axles
- (2) 10,000 lb. Axles (4 Wheels)
- Tires-235/75R17.5, Load Range J, 18-Ply
- 17.5" Wheels, 8-Bolt
- Electric Brakes
- Forward Self-Adjusting Brakes
- Oil Bath Hubs
- 34" Axle Spacing

Lights/Wiring

- Rubber Grommet Mounted LED Lights
- Sealed Modular Wiring Harness

Standard Features

- Limited Lifetime Frame Warranty-10 years
- One-Year Full Warranty
- 10 Year Suspension Warranty
- Weatherproof Registration Holder
- Two-Component Polyurethane Primer and Paint
- Trailer Color: Equipment Black
- Ramp Color: Equipment Red

GAWR (lbs.)	GVWR (lbs.)	Weight (lbs.)	Capacity (lbs.)	Deck Width (in.)	Deck Length (ft.)
20,000	24,410	4,410	20,000	82"	18'
20,000	24,900	4,900	20,000	82"	20'

Other Options May Be Available. Ask Your Dealer or Visit our Website.

Listed GVWR, weight and dimensions are for reference only. Manufacturer reserves the right to change models and specifications as they see fit. See our website or your local authorized dealer for more information.

Options	T-12D	T-16D	T-20D	T-24D
TONGUE/HITCH				
Hydraulic Surge Brakes with Free Backing (Check Local D.O.T Laws)	•			
2-5/16" Ball Coupler	•			
2-5/16" Ball Coupler (25K Capacity)		•	•	•
3" Pintle Ring	•			
4-Way Flat Electrical Plug	•			
6-Pole Round Electrical	•	•	•	•
7-Pole Round Electrical	•	•	•	•
12k Electric Over Hydraulic Jack with Battery	•	•	•	•
12k Spring Foot Jack		•	•	•
25k Two-Speed Jack	•	•	•	•
Lockable Storage Tray Lid (Storage Tray Standard)	•	•	•	•
Mesh in A-Frame of Tongue	•	•	•	•
A-Frame Gooseneck (2-5/16" coupler) 84" swing clearance, 39" hitch height/truck bed height (please call if your measurement is different). A toolbox, toolbox lid and dual 12k jacks are included.	•	•	•	•
Spare Tire Mount on A-Frame Gooseneck (Spare Tire Sold Separately)	•	•	•	•
A-Frame Gooseneck Toolbox (lockable) Mounted Between the Gooseneck Uprights, Includes a Chain Bar	•	•	•	•
MAIN DECK/BEAVERTAIL				
Pallet Fork Holders	•	•	•	•
Additional D-Ring Tie-Downs	•	•	•	•
Rub Rail and Stake Pockets in Lieu of D-Rings	•	•	•	•
Additional Stake Pockets	•	•	•	•
Apitong Wood Decking Upgrade	•	•	•	•
7-Gauge Steel Deck in Lieu of Wood, with Non-Slip Grit	•	•	•	•
3/16" Diamond Plate Steel Decking. Crossmembers 12" On-Center	•	•	•	•
Full Width Deck in Front of Fender (curbside only)	•	•	•	•
Full Width Deck in Front of Fender (roadside only)	•	•	•	•
Full Width Deck (102" wide) in Front of Both Fenders (not rear of fenders)	•	•	•	•
Full Width Deck (102" wide) Full Length of the Deck on Curbside and Roadside	•	•	•	•
Open Fender Option-84" I.D. between Fenders (no inside fender wall/covering)		•	•	
3-foot Wood-Topped Beavertail with 5' Angle-Iron Ramps (10 Degree Load Angle)	•	•	•	•
3-Foot Angle Iron Beavertail with 5' Angle-Iron Ramps (10 degree load angle)	•	•	•	•
Deck Side Lip Turned Down	•	•	•	•
Drill Kit Option: 500-gallon tank support, steel chock blocks, and mixer brackets. (curbside tank placement only) Ramps mounted on roadside		•	•	•
Drill Kit Option: 500-gallon tank support, steel chock blocks, and mixer brackets. (roadside tank placement only) Ramps mounted on curbside		•	•	•
Drill Kit Option: 400-gallon tank support, steel chock blocks, and mixer brackets. (curbside tank placement only) Ramps mounted on roadside		•	•	•
Side-load paver option: Dual 12k jacks mounted on the headboard, full width deck (102" wide) in front of both fenders, 2 side load ramps with ramp storage under the deck.		•	•	•

Options	T-12D	T-16D	T-20D	T-24D
SUSPENSION/TIRES AND WHEELS				
Hubodometer-Mounts on Wheel to Measure Distance Traveled	•	•	•	•
Spare Tire Mount Bracket, Mounted Curbside in Front of the Fender (Not to be used with Rub Rail)	•	•	•	•
Spare Tire and Wheel 235/85R16 Load Range F	•			
235/85R16 Load Range "G" 14-Ply Upgrade (in lieu of "F") set of Four Tires	•			
Spare Tire and Wheel 215/75R17.5 Load Range H		•		
Spare Tire and Wheel 235/75R17.5 Load Range J		•	•	•
RAMPS				
Full Width Ramp Rod with Center Ramp Support. Ramps Mounted on Curbside	•	•	•	•
Full Width Ramp Rod with Center Ramp Support. Ramps Mounted on Roadside	•	•	•	•
Wood Filled 5-Foot Ramps (Pair)	•			
Wood Filled 6-Foot Ramps with Solid Bar Ramp Hold-Ups (Pair)		•	•	•
Full Width Mesh-Top Ramps. Two ramps 48" wide x 5'-0" long each. Solid-Bar Ramp Hold-Ups with Spring Assist Included.	•			
5'-0" Ramps with Star Traction and Solid-Bar Ramp Hold-Ups	•			
6'-0" Ramps with Star Traction and Solid-Bar Ramp Hold-Ups (improves load angle by 2 degrees versus 5'-0" ramps)	•	•	•	•
6'-0" Ramps, Cleated Ladder Style with Solid-Bar Ramp Hold-Ups (improves load angle by 2 degrees versus 5'-0" ramps)	•			
PAINT/ELECTRICAL/OTHER				
8K Electric Winch with 95 feet of 5/16" cable, Mounted on the Deck Side of Headboard. Includes a Battery and Charger.	•	•	•	•
Trailer Color Options: See Standard Color Chart	•	•	•	•
Galvanizing-(Please Call for Current Cost)	•	•	•	•
Custom Paint Color: Market Price (Please Call for Cost)	•	•	•	•
Two Chock Blocks with Holders (Mounted on Rear of Fender)	•	•	•	•
Change Ramp Color from Red to Yellow, or Blue or Charcoal (No Charge for Black)	•	•	•	•