



#### All dimensions are nominal. Illustration may be shown with optional equipment.

## **Standard Features**

# Hitch/Tongue

- Adjustable Height Hitch with Bolt-on Coupler
- 3" Pintle Ring
- One-Piece Cold-Formed I-Beam Frame Rails
- Integrated Storage Tray with Lockable Lid
- 25k Bolt-On Two-peed Jack
- Battery Break-Away Kit with Tow Charger and Test Light
- 7-Pole Round Electrical Plug
- Safety Chains with Hooks

#### Frame/Deck

- 102" Load Width
- 33.5" Deck Height (Fully Loaded)
- 20' Main Deck Length
- 10" I-Beam Main Frame
- 3" Jr. I-Beam Crossmembers
- 2" Nominal White Oak Deck
- D-Ring Tie-Downs (4 Per Side)

## Ramps/Tail

- 5' Steel Angle-Iron Beavertail (14° Load Angle)
- 5' x 21" Ladder Style Angle Iron Cleated Ramps (14° Load Angle)
- Two-Way Spring-Assist Ramps
- Beavertail to Deck Transition Wood Protectors

### Axles/Suspension

- Hutchens 9700 Adjustable Suspension
- (2) 16,000 lb. Axles (8 Wheels)
- Tires -215/75R17.5 Load Range H, 16-Ply
- 17.5" Wheels, 8-Bolt, Hub-Piloted
- Electric Brakes Only
- Oil Bath Hubs
- 49" Axle Spacing

#### Lights/Wiring

- Rubber Grommet Mounted LED Lights
- Sealed Modular Wiring Harness

#### **Standard Features**

- Limited Lifetime Frame Warranty-10 years
- One-Year Full Warranty
- 5 Year Suspension Warranty
- Weatherproof Registration Holder
- Two-Component Polyurethane Primer and Paint
- Trailer Color: Equipment Black
- Ramp Color: Equipment Red

GAWR (lbs.)	GVWR (lbs.)	Weight (lbs.)	Capacity (lbs.)	Deck Width (in.)	Deck Length (ft.)
30,000	38,300	8,300	30,000	102"	20'

Options	T-20LP	T-24LP	T-30LP
TONGUE/HITCH			
6' Tongue Length in Lieu of Standard 5' Tongue		•	•
7' Tongue Length in Lieu of Standard 5' Tongue		•	•
-5/16" Ball Coupler (25k Capacity)		•	•
6-Pole Round Electrical Plug		•	•
7-Pole RV Electrical Plug	•	•	•
12k Spring Foot Jack		•	•
Dual 12k Parking Jacks (Additional 12k Jack on T-20LP & T-24LP)		•	
12k Electric Jack with Battery		•	
25k Two-Speed Parking Jack in (Lieu of Standard 12k Jack)		•	
25k Electric Jack with Battery	•	•	•
Dual 25k Two-Speed Parking Jacks (T-20LP & T-24LP)		•	
Dual 25k Two-Speed Parking Jacks (Additional 25k Jack on T-30LP)			•
Mesh in A-Frame of Tongue	•	•	•
A-Frame Gooseneck (2-5/16" coupler) 84" swing clearance, 39" hitch height/truck bed height (please call if your measurement is different). A toolbox, toolbox lid and dual 12k jacks are included.	•	•	
A-Frame Gooseneck (3" coupler) 84" swing clearance, 39" hitch height/truck bed height (please call if your measurement is different). A toolbox, toolbox lid and dual 12k jacks are included.			•
Rigid Gooseneck (King-Pin) 84" Swing Clearance, 39" King-Pin Height (Fifth Wheel Height-Please Call if your Measurement is Different) 10' Long Top Deck (White Oak Wood Standard)	•	•	•
8' x 5' Rack on Gooseneck-Mesh Platform	•	•	•
8' x 5' Rack on Gooseneck-Wood Platform	•	•	•
Spare Tire Mount on A-Frame Gooseneck (Spare Tire Sold Separately)	•	•	•
A-Frame Gooseneck Toolbox (Lockable) Mounted Between the Gooseneck Uprights, Includes a Chain Bar	•	•	•
MAIN DECK/BEAVERTAIL			
Up to 4' of Additional Deck Length, Please Call for Additional Deck Length Over 4'	•	•	•
9' Wide Deck and Beavertail	•	•	
9' Wide Deck and Beavertail			•
Apitong Wood Decking Upgrade		•	•
3/16" Diamond Steel Plate Decking, Crossmembers 12' On-Center	•	•	•
Additional D-Ring Tie-Downs	•	•	•
Rub Rail and Stake Pockets in Lieu of D-Rings	•	•	•
Additional Stake Pockets	•	•	•
Sliding Winch Track-Mounted on Curbside of the Deck-Winches Sold Separated		•	•
4' Sliding Winch Strap with Flat Hook	•	•	•
4" Weld-On Winch-Mounted on Curbside-Cargo Straps Sold Separately		•	•
4"x30' Winch Strap with Flat Hook		•	•
Trailer Step-Please Specify Location		•	•
5' Wood Topped Beavertail in Lieu of Standard 5' Angle Iron Beaver Tail	•	•	•
5'-6" Wedge Ramp Beavertail Angle Iron, (Must Be Used with Wedge Style Ramp Option Only)			
3 3 Medge Ramp beavertain ringic from financiae osca with wedge style Ramp Option Only)		_	•

Options	T-20LP	T-24LP	T-30LP
MAIN DECK/BEAVERTAIL CONTINUED			
6' Angle Iron Beavertail	•	•	•
5' Wood Topped Beavertail		•	•
7'-6" Double Brake Beavertail-Angle Iron, Option Comes with 6' Angle Iron Ramps Standard (12 Degree to 6 Degree to Deck Load Angle Transition)	•	•	•
7'-6" Double Brake Beavertail-Wood Topped, Option Comes with 6' Angle Iron Ramps Standard (12 Degree to 6 Degree to Deck Load Angle Transition)	•	•	•
Bobtail-No Beavertail	•	•	•
Bucket Well in Beavertail	•	•	•
SUSPENSION/TIRES AND WHEELS			
Hub Odometer-Mounts on Wheel to Measure Distance Traveled	•	•	•
4S/2M Two-Axle Anti-Lock Braking System-Four Wheel Sensors and Two ABS Relay Valves	•	•	
Polished Aluminum Wheels-8 Bolt, Hub Piloted		•	•
235/85R16 Load Range "G" 14-Ply Upgrade (In Lieu of "F")			•
235/75R17.5 Load Range "J" 18-Ply Tires in Lieu of Standard 215/75R17.5 Load Range "H" Tires		•	•
Spare Tire Mounting Bracket Mounted Flat on the Tongue		•	•
Spare Tire and Wheel 235/85R16 Load Range "F" 12-Ply		•	•
Spare Tire and Wheel 235/85R16 Load Range "G" 14-Ply	•	•	•
Spare Tire and wheel 215/75R17.5 Load Range "H" 16-Ply	•	•	•
Spare Tire and Wheel 235/75R17.5 Load Range "J" 18-Ply	•	•	•
RAMPS			
Third Ramp (Requires the Full Width Ramp Rod Option)	•	•	•
Full Width Ramp Rod		•	•
4'-6" Angle Iron Wedge Ramps (Pair)	•	•	•
6' Wood Topped Ramps in Lieu of Standard 6' Angle Iron Ramps in Double Break Beavertail Option (Pair)		•	•
6' x 36" Air Ramps-Angle Iron (Paid)		•	•
6' x 36" Air Ramps-Wood Topped (Pair)		•	•
6' x 36" Electric/Hydraulic Ramps-Angle Iron (Air)		•	•
6' x 36" Electric/Hydraulic Ramps-Wood Topped (Pair)		•	•
Bi-Fold Electric/Hydraulic Ramp 11' in Length and 102" Wide, Wood Topped and Provides a 9 Degree to 8 Degree to Deck Load Angle Transition (Requires a 26' Deck Minimum and the 6' Wood Topped Beavertail Option)		•	•
PAINT/ELECTRICAL/OTHER			
12K Electric Winch with 125 Feet of 3/8" Cable, Corded Remote, and Wired to the Tongue of the Trailer	•	•	•
Battery Kit with Charger for Electric Winch		•	•
Trailer Color Options: See Standard Color Chart		•	•
Galvanizing-(Please Call for Current Cost)		•	•
Custom Paint Color: Market Price (Please Call for Cost)	•	•	•